## 

## drum ECO-230l

CHARACTERISTICS	NOMINAL VALUE
Weight	7 kg.
Outer opening diameter	1332 mm.
Inner opening diameter (Di)	397 mm.
Outer opening diameter (Dext)	407 mm.
Medium opening thickness	6 mm.
Point thickness	≥ 2.5 mm.
Nominal volume	230 I.
Height (h)	1114 mm.
Maximum development of the drum	1764 mm.
Maximum diameter of the drum	561 mm.
Colour	According to Manufacturing Order.
Visual appearance	Absence of defects.
Thread	Minimum of 3 threads.
Lock	It must ensure tightness.
Marks / Signals	According to Manufacturing Order.







\*Our drums are conceived, designed and marketed to perform multiple circuits or rotations throughout their life cycle, or to be refilled or reused for the same purpose for which they were designed.

The information contained herein is based upon data to be reliable and is, to the best of our knowledge and belief, accurate. We offer it with our best intention, but as we cannot control a bad use of it, we shall not be liable for any loss, damage or injury that may occur from the use of this information. This information is not a product specification, which appears on the respective contracts and/or orders.

ID - 16.05.2022



Reyenvas, S.A. Autovía Sevilla-Málaga, Km. 5 Polígono Industrial La Red 41500 Alcalá de Guadaíra (Sevilla) España T. (+34) 95 563 15 40 comercial@reyenvas.com

🛉 @reyenvas 🔰 @reyenvas

@reyenvas@reyenvas\_sevilla

armando alvarez

