



# hilo torcido T-300

## Baler twine

PROPERTIES	VALUE	UNIT	STANDARD
<b>Dimensional characteristics</b>			
Runnage	270	m/kg	EN ISO 4167
<b>Mechanical properties</b>			
Tensile strength at break	144	kg	EN ISO 4167
Maximum elongation	10	%	EN ISO 4167
Tensile strength at knot	79	kg	EN ISO 4167
<b>Presentation</b>			
Roll weight	5	kg	-
Roll performance	1350	m	-

The information contained herein is based upon data to be reliable and is, to the best of our knowledge and belief, accurate. We offer it with our best intention, but as we cannot control a bad use of it, we shall not be liable for any loss, damage or injury that may occur from the use of this information. This information is not a product specification, which appears on the respective contracts and/or orders.

ID 19 STD - 18.05.2022



Reyenvas, S.A.  
Autovía Sevilla-Málaga, Km. 5  
Polígono Industrial La Red  
41500 Alcalá de Guadaíra (Sevilla) España  
T. (+34) 95 563 15 40  
[comercial@reyenvas.com](mailto:comercial@reyenvas.com)

 @reyenvas  
 @reyenvas  
 @reyenvas\_sevilla



 **reyenvas**  
[www.reyenvas.com](http://www.reyenvas.com)