



tutor torcido T-1200 anti-UV

Baler twine

PROPERTIES	VALUE	UNIT	STANDARD
Dimensional characteristics			
Runnage	1200	m/kg	EN ISO 4167
Mechanical properties			
Tensile strength at break	32	kg	EN ISO 4167
Maximum elongation	10	%	EN ISO 4167
Tensile strength at knot	17	kg	EN ISO 4167
Presentation			
Roll weight	5	kg	-
Roll performance	6000	m	-
Durability (*)	2	years	

(*) At a climate of 130-160 kLangley/year (for different radiation conditions or different thickness, we should be consulted).

The information contained herein is based upon data to be reliable and is, to the best of our knowledge and belief, accurate. We offer it with our best intention, but as we cannot control a bad use of it, we shall not be liable for any loss, damage or injury that may occur from the use of this information. This information is not a product specification, which appears on the respective contracts and/or orders.

ID 73 STD - 13.12.2024



Reyenvas, S.A.
Autovía Sevilla-Málaga, Km. 5
Polígono Industrial La Red
41500 Alcalá de Guadaíra (Sevilla) España
T. (+34) 95 563 15 40
comercial@reyenvas.com

 @reyenvas
 @reyenvas
 @reyenvas_sevilla



 **reyenvas**
www.reyenvas.com