

GENERAL CONDITIONS OF USE FOR FILMS IN ASPARAGUS CULTIVATION

1. INTRODUCTION

REYENVAS, S.A., has a Quality Assurance system certified in accordance with UNE-EN ISO 9001, which ensures quality in each of the production stages of our products.

REYENVAS, S.A. manufactures and markets plastic sheets with minimum guaranteed service lives depending on the type and thickness of the film.

2. DURATION TABLES

The guaranteed service life of the different sheets marketed by REYENVAS, S.A. for asparagus cultivation which comply with the conditions set out below shall be those reflected in the description of each product in the form of the number of seasons (1S, 2S, etc.). For asparagus cultivation, an agricultural season is understood to be the period from 1 December (installation) to 31 May (removal). Product stored between seasons must be kept in a place fully protected from solar radiation.

RANGE	COLOR	MINIMUM THICKNESS (*)	DURATION	RADIATION, kLy/año
REY BLACK	Black	62,5 microns	1S	140 – 160
			1S	100 – 120
			2S	80 – 100
		100 microns	2S	140 – 160
			3S	100 – 120
			4S	80 – 100
REY PRO M+	White / Black	100 microns 125 microns	3S	140 – 160
			4S	100 – 120
			6S	80 – 100
		150 microns	4S	140 – 160
			6S	100 – 120
			8S	80 – 100
REY PRO NATURE	White / Green	100 microns 125 microns	1S	140 – 160
			2S	100 – 120
			3S	80 – 100
		150 microns	2S	140 – 160
			3S	100 – 120
			5S	80 – 100
REY THERMAL	Clear	50 microns	1S	140 – 160
			1S	100 – 120
			2S	80 – 100
		100 microns	2S	140 – 160
			3S	100 – 120
			4S	80 – 100

(*) Minimum thickness refers to the Nominal Thickness of the order or contract.

These data (range, thickness and duration) must be perfectly identified in the corresponding contracts and/or orders.

For the duration of the same sheets in another area with different radiation, it is always necessary to consult the guaranteed time for the area where the product is to be installed.

3. REPLACEMENT TABLE

The quantity of plastic to be replaced in the event of premature degradation for all the previous duration-guarantee cases shall be calculated as indicated below, applying a PRO RATA TEMPORIS formula.

$$\% \text{ PLASTIC TO BE REPLACED} = 100 - \left(\frac{\text{FILM SERVICE LIFE UNTIL BREKAGE}}{\text{GUARANTEED SERVICE LIFE}} \times 100 \right)$$

The guarantee period for calculating the replacement shall be counted as one seasonal cycle from 1 December (installation) to 31 May (removal); therefore, the guaranteed service life shall be 6 months per Season.

4. RECOMMENDATIONS

Transport and Storage

- During the transport and storage, the reels must rest on smooth surface free of sharp points of profusions that could damage them
- Heavy or sharp objects (wire rolls, sticks, etc.) must not be placed on top of the reels
- Do not drag the reels during transport and/or installation, and do not rub their edges.
- To store surplus reels or products between seasons, do so in a place protected from light, heat and humidity; even better, wrap them with opaque plastic.
- The product must be collected and stored with extreme care and without applying tension or pressure to the rolled product. It is recommended to roll it up preferably by offsetting the pockets so that they do not overlap in consecutive turns, achieving a more uniform, compact and safe winding. It is also possible to leave the product between rows, provided it is perfectly protected from radiation with a fully opaque sheet.

Installation

- Do not rub the reels during installation.
- Before placing the film in the field, the soil must be prepared so that it is smooth and free of stones or clods in order to avoid the risk of perforation and film breakage.
- The film shall be placed on the soil when it is neither too dry nor too wet.
- The film should preferably be used within 6 months from delivery.
- If any defect is detected when using the film, proceed with its proper preservation and send a letter describing the problem, attaching the product label and a sample where the defect can be observed, if applicable.
- Fill the pockets with care in order to stress the weld as little as possible.

Use of agrochemicals

The use of plant-protection products may release compounds that affect the effectiveness of the stabilizers against UV radiation. Please note that the durations mentioned in this document are MINIMUM DURATIONS. Therefore, by taking proper care of the product, considerably longer durations than those guaranteed here can be achieved.

5. CLAIM HANDLING

Degradation

From a technical point of view, a film is considered degraded when the elongation value is lower than 50% of the value before installation. In practice, this is detected because the plastic becomes rigid, brittle and without resistance.

Start of guarantee

The start date of this guarantee shall be considered to be the date appearing on the last Delivery Note for the product from REYENVAS, S.A. or from its representatives, warehouses and/or distributors.

In the case of direct sea shipment without passing through a distributor, the guarantee start date shall be considered to be one month after the date of arrival of the vessel at destination.

Notice of premature degradation

All degradation claims are channelled through the Sales Department and/or distributors of REYENVAS, S.A.

As soon as premature degradation is detected, the corresponding Warehouse, Cooperative or Distributor, or REYENVAS, S.A. directly, must be informed.

Analysis results

The results of the investigations shall be communicated to the customer through the Sales representative, Cooperative, Warehouse or Distributor as soon as possible.

6. EXCLUSIONS

Breakages or incidents caused by the following are expressly excluded:

- Violent atmospheric causes (hail, strong winds, etc.)
- Mechanical breakages caused by defects in storage, transport, preservation and/or installation.
- The use of acidic products, organic solvents or agrochemicals, especially those containing Sulphur or Chlorine in their composition.
- Any other claim that does not comply with the recommendations described in section 4.
- Claims without product delivery or purchase documentation, especially the Delivery Note.

Liability of REYENVAS, S.A.

The liability of REYENVAS, S.A. shall in all cases be limited to the replacement of the corresponding plastic in the quantities defined according to sections 2 and 3.

In no other case shall this guarantee give rise to any other type of compensation.