

## GENERAL CONDITIONS OF USE FOR FILM IN CULTIVATING ASPARAGUS

### 1. INTRODUCTION

REYENVAS, S.A. has a quality assurance system certified according to standard UNE-EN ISO 9001, which ensures quality in each phase of the production of our products. REYENVAS, S.A. manufactures and markets plastic sheets with a guaranteed minimum duration, depending on the type and thickness of the film.

### 2. DURATION TABLES

The guaranteed duration of the different sheets marketed by REYENVAS, S.A. for cultivating asparagus that meet the conditions set out later will be reflected on each product description in form of number of seasons (1C, 2C, etc.). It is understood by agricultural season for cultivating asparagus the period between the 1<sup>st</sup> of December (installation) and the 31<sup>st</sup> of May (removed). The stored product between seasons must be maintained in a totally protected place against solar radiation.

<b>GAMMA</b>	<b>COLOUR</b>	<b>MINIMAL THICKNESS (*)</b>	<b>DURATION</b>	<b>RADIATION kLy/año</b>
<b>REY BLACK</b>	Black	62,5 microns	1C	140 – 160
			1C	100 – 120
			2C	80 – 100
		100 microns	2C	140 – 160
			3C	100 – 120
			4C	80 – 100
<b>REY PRO EKO</b>	White / Black	100 microns 125 microns	1C	140 – 160
			2C	100 – 120
			3C	80 – 100
		150 microns	2C	140 – 160
			3C	100 – 120
			5C	80 – 100
<b>REY PRO M</b>	White / Black	100 microns 125 microns	3C	140 – 160
			4C	100 – 120
			6C	80 – 100
		150 microns	4C	140 – 160
			6C	100 – 120
			8C	80 – 100
<b>REY PRO M+</b>	White / Black	100 microns 125 microns	3C	140 – 160
			4C	100 – 120
			6C	80 – 100
		150 microns	4C	140 – 160
			6C	100 – 120
			8C	80 – 100
<b>REY PRO NATURE</b>	White / Green	100 microns 125 microns	1C	140 – 160
			2C	100 – 120
			3C	80 – 100
		150 microns	2C	140 – 160
			3C	100 – 120
			5C	80 – 100
<b>REY PRO MTH+</b>	White / Thermal / Black	175 microns	3C	140 – 160
			4C	100 – 120
			6C	80 – 100

REY THERMAL	Natural	50 microns	1C	140 – 160
			1C	100 – 120
			2C	80 – 100
		100 microns	2C	140 – 160
			3C	100 – 120
			4C	80 – 100
REY PRO TR	Black / White / Black	75 microns	1C	80 – 160

(\*) Minimal Thickness makes reference to the Nominal Thickness of the order or contract.

These data (gamma, thickness and duration) must remain perfectly identified on the corresponding contracts and/or orders.

For the duration of the same sheets in another area with different, it is necessary to always ask the time guaranteed for the area where you are installing the product.

### 3. REPLACEMENT TABLE

The amount of plastic to be replaced in the event of premature degradation in all of the cases of duration guarantees set out above will be calculated as shown below, on a PRO RATA TEMPORIS basis.

$$\% \text{ FILM TO BE REPLACED} = 100 - \left( \frac{\text{LIFETIME OF THE FILM UNTIL DEGRADATION}}{\text{GUARANTEED LIFETIME}} \times 100 \right)$$

The warranty period for the calculation of the replacement will be made by counting a season cycle from December 1 (installation) until May 31 (withdrawal), so that the guaranteed life time will be 6 months per season.

### 4. RECOMMENDATIONS

#### Transport and Storage

- During transport and storage, the reels must rest on a smooth surface with no protruding or sharp points that could damage them.
- Do not place any heavy or sharp objects (rolls of wire, stakes, etc.) on top of the reels.
- Do not drag the reels during transport and/or installation or scrape their edges.
- For storing leftover reels or material between seasons, do it in a place protected against light, heat and humidity, and even better wrap them in opaque plastic.
- The product must be collected and stored with extreme caution and without exerting stress or pressure on the rolled product. It recommends to roll it up preferably by swinging the pockets in order that do not match each other in consecutive laps, getting a more homogeneous, compact and safe winding. You can also leave the product between lines, provided that it is perfectly protected from radiation with a completely opaque sheet.

#### Installation

- Do not scrape the reels during installation.
- Previous to the placement of the film on the field, the earth must be prepared in order that it remains flat and without stones or lumps so that it can avoid any risks of perforation or breakage of the film.
- The film will be placed on the soil when it is neither too dry nor too wet.
- The film must be used preferably before 6 months since its delivery.
- If using the film some defect is detected on it, proceed to its adequate conservation and send a letter describing what is happened. Please add a product label as well as a sample of the product where you can appreciate the defect, if proceed.
- Fill the pockets with caution for forcing the welding as least as possible.

#### Use of agrochemical

The use of phytosanitary products can release compounds that affect the effectiveness of the stabilizers protecting the plastic against UV radiation. Keep in mind that the durations mentioned in this document refer to the MINIMUM DURATIONS. By following the recommendations above, it is possible to obtain considerably longer durations than those guaranteed here.

### 5. CLAIMS PROCESSING

#### Degradation

From the technical point of view, a film is considered degraded when its elongation value is less than 50% of its value before placement. In practice it detects it because the film becomes rigid, brittle and without resistance.

**Start of guarantee period**

As start date of the guarantee will be considered the one that appears on the last delivery note once the product has left REYENVAS, S.A. or its representatives, warehouses and/or distributors. In case of direct sea transport with no mediation by a distributor, the start of the guarantee period will be one month after the date of vessel arrival at destination.

**Notification of premature degradation**

All claims related to degradation must be handled by the REYENVAS, S.A. Sales Department or Distributors.

Notify the corresponding warehouse, cooperative, distributor or REYENVAS, S.A. directly, as soon as premature degradation is detected.

**Results of the analyses**

The client will be notified with the results of the investigations by the sales representative, cooperative, warehouse or distributor as soon as possible.

**6. EXCLUSIONS**

Expressly excluded, breakage and claims produced by:

- Extreme weather conditions (hail and strong winds)
- Mechanical damage caused by deficient storage, transport, conservation and/or installation.
- The use of acids, organic solvents or chemicals, especially those containing in its composition sulfur or chlorine
- Any other claim that does not comply with the recommendations described in Section 4.
- Claims that do not include all the requested documentation, in particular, the delivery note.

**Responsibility of REYENVAS, S.A.**

The responsibility of REYENVAS, S.A. shall be limited in all cases to replacing the corresponding plastic in the amounts specified in Sections 2 and 3. In no other case shall this guarantee affect any other type of compensation.